




Denominación: **CHIPBOARD SCREW DIN-7505-A, POZIDRIV, COUNTERSUNK 90° HEAD, THREAD 40°, POINT 25°, WAXED, ZINCPLATED**

## 1. CHARACTERISTICS

- \* For use in any type of wood carpentry assemblies.
- \* Double Countersunk 90° Head
- \* Thread 40°
- \* 25° tip that allows direct drilling of the wood.
- \* Applications: Fixing of brackets, unions, fittings, uprights, on wood with previous drilling.  
Union of hardwoods between themselves.

## 2. MATERIAL

- \* Special steel for heat treatment C1022 - SAE J403.
- \* Finished: Zincplated CR+3 5µm.



## 3. SCREW SIZES

Diameter		Ø 2,5	Ø 3,0	Ø 3,5	Ø 4,0	Ø 4,5	Ø 5,0	Ø 6,0
A	Ø Head	4,60 ÷ 5	5,60 ÷ 6	6,60 ÷ 7	7,50 ÷ 8	8,40 ÷ 9	9,40 ÷ 10	11,30 ÷ 12
D2	Ø External thread	2,30 ÷ 2,50	2,70 ÷ 3,05	3,20 ÷ 3,55	3,70 ÷ 4,05	4,20 ÷ 4,55	4,70 ÷ 5,05	5,70 ÷ 6,05
D1	Ø Internal thread	Ref. 1,60	1,70 ÷ 1,90	2,00 ÷ 2,20	2,25 ÷ 2,50	2,45 ÷ 2,70	2,70 ÷ 3,00	3,40 ÷ 3,70
p	Thread Pitch	1,10	1,40	1,60	1,80	2,00	2,20	2,60
L	Screw Length	10 ÷ 25	12 ÷ 40	16 ÷ 50	16 ÷ 70	20 ÷ 80	20 ÷ 120	40 ÷ 220
	Pozidriv Bit N°	PZ1	PZ1	PZ2	PZ2	PZ2	PZ2	PZ3

## 4. THREAD LENGTHS

Screw Length	Ø 2,5	Ø 3,0	Ø 3,5	Ø 4,0	Ø 4,5	Ø 5,0	Ø 6,0
Up to 50 mm.	Full	Full	Full	Full	Full	Full	Full
Up to 60 mm.				36 mm.	36 mm.	36 mm.	36 mm.
Up to 70 mm.				42 mm.	42 mm.	42 mm.	42 mm.
Up to 80 mm.					48 mm.	48 mm.	48 mm.
Up to 90 mm.						54 mm.	54 mm.
Up to 100 mm.						70 mm.	70 mm.
From 100 mm.						70 mm.	70 mm.

NOTE: The information reflected in this Technical Data Sheet is informative, without any contractual value, the data is indicative. MAREFIX, S.L. reserves the right to modify the design of its products without prior notice